

Compact laboratory balance KERN EWJ



Vaakatalo Oy  
 Vestonkatu 11  
 33580 TAMPERE  
 info@vaakatalo.com  
 www.vaakatalo.com  
 Puh. 020 73 51 500



High-quality precision balance with automatic internal adjustment, also with EC type approval [M]

### Features

- Easy to use: All primary functions have their own key on the keypad
- Automatic internal adjustment, time-controlled every 2 h, guarantees high degree of accuracy and makes the balance independent of its location
- Capacity display: A bargraph display lights up to show how much of the weighing range is still available
- KERN EWJ-H/-M: USB data interface for transferring weighing data to the PC, printer etc.
- KERN EWJ-SM: Cost-effective variant without data interfaces
- KERN EWJ 300-3, 600-2M, 600-2SM: Draught shield standard, Weighing space W×D×H 134×128×80 mm
- **KERN EWJ 300-3H**: Large glass draught shield with 3 sliding doors for easy access to the items being weighed. Weighing space W×D×H 155×175×217 mm
- Protective working cover included with delivery


### Technical data

- Large LCD display, digit height 16,5 mm
- Dimensions weighing surface
  - A** Ø 80 mm, stainless steel
  - B** Ø 120 mm, stainless steel
  - C** Ø 135 mm, stainless steel, see larger picture
  - D** W×D 155×145 mm, stainless steel
- Overall dimensions (without draught shield) W×D×H
  - A, B** 220×315×90 mm
  - C** 220×315×105 mm
  - D** 215×330×105 mm
- Overall dimensions (incl. draught shield) W×D×H
  - EWJ 300-3, 600-2M, 600-2SM: 220×340×180 mm
  - EWJ 300-3H: 220×340×321 mm
- Permissible ambient temperature
  - KERN EWJ: 15 °C/35 °C
  - KERN EWJ-M: 15 °C/30 °C

### Accessories

- Protective working cover, scope of delivery 5 items, KERN EWJ-A04S05
- Internal rechargeable battery pack, operating time up to 20 h without backlight, charging time approx. 12 h, KERN KFB-A01
- KERN EWJ-H/-M: Software BalanceConnection, for flexible recording or transmission of measured values, in particular also to Microsoft® Excel or Access as well as transfer of this data to other Apps and programs, for more details see the internet, Scope of supplies: 1 CD, 1 license, KERN SCD-4.0
- RS-232/WiFi adapter for wireless connection to networks and WiFi capable devices, such as tablets, laptops or smartphones, KERN YKI-03
- RS-232/Ethernet adapter for connection to an IP-based Ethernet network, KERN YKI-01
- Further details, plenty of further accessories and suitable printers see *Accessories*

#### STANDARD



#### OPTION



#### FACTORY



Model	Weighing capacity [Max]	Readability	Verification value	Minimal load	Linearity	Weighing plate	Verification	Option
	[g]	[d]	[e]	[Min]	[g]		MD KERN	DAkKS Calibr. Certificate
KERN	g	g	g	g	g		KERN	DAkKS KERN
EWJ 300-3	300	0,001	-	-	± 0,005	A	-	963-127
EWJ 300-3H	300	0,001	-	-	± 0,005	A	-	963-127
EWJ 3000-2	3000	0,01	-	-	± 0,05	C	-	963-127

Note: For applications that require verification, please order verification on at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.

EWJ 600-2SM	600	0,01	0,1	0,5	± 0,03	B	965-216	963-127
EWJ 600-2M	600	0,01	0,1	0,5	± 0,03	B	965-216	963-127
EWJ 6000-1SM	6000	0,1	1	5	± 0,3	D	965-217	963-128
EWJ 6000-1M	6000	0,1	1	5	± 0,3	D	965-217	963-128

- 
**Internal adjusting:**  
 Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)
- 
**Network interface:**  
 For connecting the scale to an Ethernet network
- 
**Suspended weighing:**  
 Load support with hook on the underside of the balance
- 
**Adjusting program CAL:**  
 For quick setting up of the balance's accuracy. External adjusting weight required
- 
**KERN Communication Protocol (KCP):**  
 It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems
- 
**Battery operation:**  
 Ready for battery operation. The battery type is specified for each device
- 
**Easy Touch:**  
 Suitable for the connection, data transmission and control through PC or tablet.
- 
**Rechargeable battery pack:**  
 Rechargeable set
- 
**Memory:**  
 Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.
- 
**GLP/ISO log:**  
 The balance displays weight, date and time, independent of a printer connection
- 
**Universal plug-in power supply:**  
 with universal input and optional input socket adapters for  
 A) EU, CH, GB  
 B) EU, CH, GB, USA  
 C) EU, CH, GB, USA, AUS
- 
**Alibi memory:**  
 Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.
- 
**GLP/ISO log:**  
 With weight, date and time. Only with KERN printers.
- 
**Plug-in power supply:**  
 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available
- 
**KERN Universal Port (KUP):**  
 allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WLAN, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort
- 
**Piece counting:**  
 Reference quantities selectable. Display can be switched from piece to weight
- 
**Integrated power supply unit:**  
 Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
- 
**Data interface RS-232:**  
 To connect the balance to a printer, PC or network
- 
**Recipe level A:**  
 The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out
- 
**Weighing principle: Strain gauges**  
 Electrical resistor on an elastic deforming body
- 
**RS-485 data interface:**  
 To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible
- 
**Recipe level B:**  
 Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display
- 
**Weighing principle: Tuning fork**  
 A resonating body is electromagnetically excited, causing it to oscillate
- 
**USB data interface:**  
 To connect the balance to a printer, PC or other peripherals
- 
**Totalising level A:**  
 The weights of similar items can be added together and the total can be printed out
- 
**Weighing principle: Electromagnetic force compensation**  
 Coil inside a permanent magnet. For the most accurate weighings
- 
**Bluetooth\* data interface:**  
 To transfer data from the balance to a printer, PC or other peripherals
- 
**Percentage determination:**  
 Determining the deviation in % from the target value (100 %)
- 
**Weighing principle: Single cell technology:**  
 Advanced version of the force compensation principle with the highest level of precision
- 
**WiFi data interface:**  
 To transfer data from the balance to a printer, PC or other peripherals
- 
**Weighing units:**  
 Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details
- 
**Verification possible:**  
 The time required for verification is specified in the pictogram
- 
**Control outputs (optocoupler, digital I/O):**  
 To connect relays, signal lamps, valves, etc.
- 
**Weighing with tolerance range:**  
 (Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model
- 
**DAkkS calibration possible (DKD):**  
 The time required for DAkkS calibration is shown in days in the pictogram
- 
**Analogue interface:**  
 to connect a suitable peripheral device for analogue processing of the measurements
- 
**Hold function:**  
 (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value
- 
**Factory calibration (ISO):**  
 The time required for Factory calibration is shown in days in the pictogram
- 
**Interface for second balance:**  
 For direct connection of a second balance
- 
**Protection against dust and water splashes IPxx:**  
 The type of protection is shown in the pictogram.
- 
**Package shipment:**  
 The time required for internal shipping preparations is shown in days in the pictogram
- 
**Pallet shipment:**  
 The time required for internal shipping preparations is shown in days in the pictogram

\*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.