

NS20 Weighing Indicators

T-Scale



Features

- 4.3-inch color display** with graphic interface
- The Maximum storage 999 PLU**, which can be quickly called by scanning
- Support** multi-language
- Multi-user** permission management
- Flexible positioning**, can be placed on the table or wall use
- Standard RJ45 network communication**, data can be uploaded/sent via Ethernet
- Standard USB storage**, you can import/export data via U disk
- Standard RS232 interface** can be connected to PC or printer

Background management software: with product management, customized print format, Report management, online update and other functions


Technical Data

- Display:** 4.3 inch color LCD resistive touch display, resolution 480x 272 px
- Power:** AC adapter (100~240VAC/12V2500mA), rechargeable battery (lithium batteries 7.4V/5200mAh).
- Memory:** 999 PLU and 30,000 weighing data
- Operation temperature:** -10 °C/40 °C
- Interface:** RS232x1, USB2.0 x1, RJ45x1, Loadcellx1
- Keyboard:** 33 membrane keys

Accessories

- Bluetooth 5.0 can transfer data to PC or Bluetooth-configured device
- Label printer
- Ticket printer
- 3 color light tower
- Scanner

Standard



Optional



VAAKATALO

Vaakatalo Oy
Vestonkatu 11
33580 TAMPERE
info@vaakatalo.com
www.vaakatalo.com

Model	NS20
Housing	Stainless steel 304
Dimensions	270×188×166mm
Net weight	2.5kg
nmax.	7500 for approved, 30000 for none approved
Load cell input resistance	43~1600 ohms
Load cell excitation voltage	5VDC
Vmin(only for approval)	1.5uV
Cable length	461m/mm ²
Load cell connector	7pin

* Specification to change without notice