

3590EGTT\_NEW

3590EGTT Touch Screen weight indicator for industrial applications



Totally configurable touch screen weight indicator for advanced weighing systems. The 3590EGTT indicator, other than the chosen weighing programme, has an area for the development of specific application programmes, integrated debuggers and programming tools for PCs. Advanced weight indicator, AISI304 stainless steel with resistive touch screen display, suitable for any industrial application. It can display all of the weighing data and with the customisation of the screens, simplifying the user operations. Fitted with 3 serial ports, transmission protocols for data communication, completely configurable printouts, integrated alibi memory, and port for connection to barcode/badge reader. CE-M approvable (OIML R-76 / EN 45501, OIML R-51 - OIML R-61 - MID for dynamic check weigher AWI).

Working in cooperation with:

**VAAKATALO OY**

LUKINKATU 10 - 33580 - TAMPERE - FINLAND  
Tel. 00358-207351500  
info@vaakatalo.com

**The best solution  
for advanced industrial  
applications**



## MAIN FEATURES

- Resistive backlit 5,7" (120x90mm) color touch screen graphic display, suitable for use with gloves.
- Multilanguage software available in: Italian, English, German, French and Spanish. Possibility to insert a personal translation thanks to the new "CUSTOM LANGUAGE TOOL" software.
- 3-way high brightness LED crosslight.
- 15-key alphanumerical mechanical keyboard.
- Selectable QWERTY, AZERTY or QWERTZ keyboard integrated in the touch screen.
- IP68 AISI304 stainless steel case.
- Dimensions: 328x186x144 mm.
- As standard fitted with an adjustable bracket, for bench or wall mounting. Real time clock and permanent data storage.
- Supplied with alibi memory, integrated on the motherboard.
- Slot for built-in micro SD for recording the configuration, logos, and customized screens (upon request).
- Functions available with DINI TOOLS Utility Software, even from remote way (WEBSERVER mode via internet).
  - Configuration, data entry and print formatting.
  - Recording and transmitting of all the information on PC.
  - Complete retrieval of the configuration.
  - Instrument calibration with numeric values.
  - Customization of the screens.
  - Development environment for custom programmes through specific programming language.
- 24-bit A/D converter, 4 channels, up to 3200 conv./sec. and up to 8 signal linearisation points.
- 4 independent analogue channels (up to 2 in the E-AF03 version) for connecting to analogue loadcells.
- Connects with up to 16 analogue load cells of 350 Ohm (45 load cells of 1000 Ohm) and with the main digital load cells available on the market (mod. E-AF03).
- Management of the most common digital load cells for weigh bridges (with DIGIKIT option and AF03GT firmware), also for CE-M approved applications.
- Up to 10.000e OIML or 3 x 3000e @ 0,3  $\mu$ V/e CE-M legal for trade.
- Up to 1.000.000 displayable divisions for internal factory use, with internal resolution up to 3.000.000 points.
- Connectable to printers and labellers with free programming of the printout formats.
- 110-240 Vac power supply.

## MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76
- OIML R-51 - MID automatic checkweighers (require "CHECK" firmware option)
- OIML R-61 - MID automatic filling machines (require "BATCH1-R61" firmware option)
- OIML R134 (AF09)
- Australian legal for trade certificate of approval (NMI S788)

## APPLICATION SOFTWARE

- SUPPLIED AS STANDARD:
- AF01: Totalization and formula weighing

### OPTIONAL:

- AF02: Pieces/quantity counting
- AF03: Weighbridges - Input/Output vehicle
- AF04: Statistical checking of prepackaged goods
- AF05: Price computing and industrial labelling
- AF08: Wheel and axle static weighing with 2 or various platforms
- AF09: Dynamic and static axle weighing with 2 platforms
- BATCH1: Single product dosage systems in loading and unloading
- BATCH: Multicomponent dosage systems in loading and unloading (IOEXPB board must be included)
- BATCH-R61: Single product dosage systems in loading and unloading

## CUSTOMISED APPLICATIONS

- Thanks to the integrated development area, fully customized applications can be created autonomously:
  - Specific
- weighing programmes according to customer requirements
  - Customized weighing programmes for terminal replacement in
- pre-existing systems
  - wizards, operator messages
  - serial port management, protocols customization
  - digital I/O full management
  - sequential or simultaneous automations
  - data entry, custom archives

Dini Argeo can offer the service of custom development programs.

## AVAILABLE LANGUAGES

- Menu selectable languages:  
IT, EN, FR, DE, ES, PT, PL \*


\* Polish available only on EGT-AF01, EGT-AF02, EGT-AF03, EGT-AF04, EGT-AF09, EGT-BATCH1, EGT-BATCH

Code pages available for the translation of messages and screens, using the Custom Language Tool program (downloadable in the Download section):

- Windows 1252: EN, GA, IT, NO, PT, ES, SV, DE, FI, IS, FR, NL, SL
- Windows 1250: PL, CS, SK, HU, SL, SH, RO, SQ, EN, DE
- Windows 1251: RU, UK, BE, BG, SR, MK, EN
- Windows 1253: EL, EN
- Windows 1258: VI, EN, FR

## CUSTOMIZABLE SCREENS

- Thanks to the programmable Touch Screen Display, you can create custom-made interfaces for any application:



- The "Dini Display Tool" is a PC software which allows you to quickly customize the TOUCH SCREEN.



## IDEAL FOR DIGITAL APPROVED WEIGHBRIDGES

- The 3590EGT indicator with the AF03GT firmware manages the most common digital load cells for weigh bridges, even for CE-M approved applications:

Dini Argeo RCPTD

Dini Argeo RCD

Rice Lake RL5416D/RL5426D

Sensocar SP/CS

Scaime CB50X-DL

Flintec RC3D

HBM C16i (requires HBM junction box and RS422 converter\RS485)

*For a complete list of supported load cells, refer to the AF03GT Weighing Program Technical Manual.*

For efficient handling and optimal protection of digital load cells, we recommend the use of the DIGIKIT option.

## I/O SECTION

- 2 RS232 serial ports, for connection to printer, PC or PLC, radio module and optional interfaces.
- 1 RS232/RS485 serial port, for connection to weight repeater, remote scale, badge reader or digital load cells.
- Fitted keyboard emulation input, for barcode/badge readers or external PC keyboard, through cable with mini DIN connector (optional).
- 4 optoisolated outputs.
- 2 optoisolated inputs.
- Modbus RTU Interface.
- Analog output DAC16O needs the expansion board IOEXPB.

Optionals:

- External Profibus or Modbus/TCP, interface, for automation management.
- External Profinet, Ethernet/IP, EtherCAT, CANopen or DeviceNet interface (optional, only with standard AF01 weighing program).
- Bluetooth connection, for quick wireless programming of the activities and the formulas, through PC or tablet.

DETAIL 1



DETAIL 2



DETAIL 3





[www.diniargeo.com](http://www.diniargeo.com)

“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 843418

**VAAKATALO OY**

LUKINKATU 10 - 33580 - TAMPERE - FINLAND

Tel. 00358-207351500

[info@vaakatalo.com](mailto:info@vaakatalo.com)

SALES AND TECHNICAL ASSISTANCE SERVICE